

ΕΚΛΟΓΗ ΚΑΛΩΔΙΩΝ / ELECTRIC CABLE SELECTION
ΑΠΕΥΘΕΙΑΣ ΕΚΚΙΝΗΣΗ / D.O.L. CONNECTION

ΙΣΧΥΣ / VOLT 380 V		ΔΙΑΤΟΜΗ ΚΑΛΩΔΙΩΝ / CABLE X- SECTION 2 Χ NYΥ (3 xmm ²)												ΠΑΡΑΛΛΗΛΑ ΚΑΛΩΔΙΑ / PARALLEL CABLES 6 x...mm ²					
		2,5	4	6	10	16	25	35	50	70	95	120	150	35	50	70	95	120	150
3	2,2	190	300	460															
4	3	150	240	360															
5,5	4	110	170	260	450														
7,5	5,5	80	130	190	340	540													
10	7,5	60	100	150	250	410													
13	9,2	50	80	120	205	330	510												
15	11		60	100	170	280	440												
20	15			80	130	210	330	460	660										
25	18,5				100	170	260	370	530										
30	22				90	140	220	310	440										
35	26					120	190	270	380	540									
40	30					100	170	230	330	460				475					
50	37							190	270	380	520			380	540				
60	45							160	230	320	440	550		324	460	640			
75	55							120	170	240	330	410	530	240	340	480	660		
90	66							110	150	220	290	370	470	210	310	430	580		
100	75							95	140	190	270	330	425	190	270	390	540	660	
125	90								110	160	220	275	340	160	220	310	400	550	
150	110									130	180	220	290	130	190	260	360	440	580
180	132										150	190	240	110	160	210	300	380	480
200	150										130	170	220	100	140	200	270	340	440
225	165											150	190			180	220	300	380
250	185												170				200	260	340
275	200												160				185	230	260

Οι παραπάνω τιμές αναφέρονται σε πτώση τάσης 3% και θερμοκρασία 25 β. κελσίου

The above figures, are valid for 3% voltage drop and temperature up to 25 degrees Celcius.